

US009636476B2

(12) United States Patent

Amarasinghe

(10) Patent No.: US 9,636,476 B2

(45) **Date of Patent:** May 2, 2017

(54) **HEADGEAR**

(71) Applicant: ResMed Limited, Bella Vista, New

South Wales (AU)

(72) Inventor: Amal Shirley Amarasinghe, West

Pennant Hills (AU)

(73) Assignee: **RESMED LIMITED**, Bella Vista (AU)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 853 days.

(21) Appl. No.: 13/938,807

(22) Filed: Jul. 10, 2013

(65) Prior Publication Data

US 2013/0319418 A1 Dec. 5, 2013

Related U.S. Application Data

(60) Continuation of application No. 12/805,787, filed on Aug. 19, 2010, now Pat. No. 8,505,538, which is a (Continued)

(51) Int. Cl.

 A61M 16/06
 (2006.01)

 A62B 18/08
 (2006.01)

 A61M 25/02
 (2006.01)

(52) U.S. Cl.

CPC **A61M 16/0683** (2013.01); **A62B 18/084** (2013.01); **A61M** 2025/022 (2013.01);

(Continued)

(58) Field of Classification Search

None

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

RE20,211 E 12/1936 Motsinger 4,099,524 A 7/1978 Cueman et al. (Continued)

FOREIGN PATENT DOCUMENTS

EP 0 747 078 A2 12/1996 EP 1 020 201 A2 7/2000 (Continued)

OTHER PUBLICATIONS

European communication corresponding EP Appln No. 10 183 527.8-1662, mailed Jun. 13, 2013, 3 pages.

(Continued)

Primary Examiner — Rachel Young
(74) Attorney, Agent, or Firm — Nixon & Vanderhye,
PC

(57) ABSTRACT

A mask assembly suitable for the treatment of sleep disordered breathing, comprising: a mask to provide pressurized air to a patient; upper and lower slot features located on each side of the mask; a headgear assembly, comprising: a back portion; a pair of upper straps provided to the back portion, each upper strap having a loop portion and a hook portion at a free end thereof for releasably attaching to the loop portion, each lower strap having a loop portion and a hook portion, each lower strap having a loop portion and a hook portion at a free end thereof for releasably attaching to the loop portion; and a connection region of each loop portion of each strap, the connection region being adapted to receive a respective hook portion, the connection region being wider than each respective hook portion along each respective hook portion's entire length.

55 Claims, 7 Drawing Sheets

